

PRODUCT SPECIFICATION SHEET



LUMINAIRES • LAMPS • ELECTRICAL • AV

Cape Town Showroom (Head Office): 9 Racecourse Road, Milnerton, 7441 | Tel: +27 (0) 21 528 8400

Johannesburg Showroom: 10 Milkyway Avenue, Linbro Business Park, Sandton, 2065 | Tel: +27 (0) 11 608 2970

eurolux
Lighting your way



www.eurolux.co.za

BARCODE: 6007328328711	PACK SIZE: 12
COLOUR: WHITE	WIDTH: 50mm
MATERIAL: Epoxy Powder Coated	DEPTH: 80mm
IP RATING: 20	LAMP TYPE: Excluding 1 x G13 max 58W T8 Fluorescent Tube
	PRIMARY VOLTAGE: 220V - 240V (50/60Hz)
ADDITIONAL INFO:	Magnetic Ballast: 1 x 58W Including Starter Not Dimmable Spare ELT Ballast Available Photometrics Available

[DOWNLOAD DRAWING](#)

[DOWNLOAD MANUAL](#)

[DOWNLOAD IES FILES](#)

PRODUCT IMAGES:

PR38 IES DIAGRAM

Light output: =149.5 lm
Beam spread: =4 839.1 cd/klm
Power: =4 W
Dimensions: -115x115x0 mm

The IES diagram shows a beam spread of approximately 18 degrees, with light intensity values ranging from 1000 to 4000 cd/klm.

PR38 CAD DIAGRAM

Dimensions: 1540mm (length), 80mm (depth), 50mm (width).